

CAMERA

TD-7421TM3

2MP Full-color HD Analog Bullet Camera



- 1080P real-time image, high resolution, true color
- AHD / TVI / CVI lossless HD video output
- Support 960H CVBS output
- Up to 800 TVL resolution
- CMOS progressive scan, perfectly capturing the moving object
- Support OSD menu
- High speed, long distance and real time transmission
- 24/7 full color imaging
- LED can be turned on or off automatically
- Support noise reduction function
- 20 ~ 30m LED distance
- IP67
- Support COC



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>


Fax: +86-755-33104777

E-mail: overseas@tvt.net.cn

SPECIFICATIONS

| Model | TD-7421TM3 |
|--------------------------|--|
| Specifications | |
| Camera | |
| Image Sensor | 1 / 2.8 "CMOS |
| Resolution | 2MP |
| Image Size | 1920 x 1080 |
| Video Output | AHD / TVI / CVI / CVBS |
| Image System | PAL / NTSC |
| Electronic Shutter | Auto |
| LED Distance | 20 ~ 30 m |
| Frame Rate | 30fps(60Hz); 25fps (50Hz) |
| Min. Illumination | 0 lux (LED ON) |
| Lens | 3.6 mm (2.8mm optional) |
| Lens Mount | M12 |
| S / N Ratio | ≥52dB (AGC OFF) |
| Ingress Protection | IP 67 |
| Functions | |
| Function Control | OSD (COC Control) |
| Smart LED | Manual or Auto mode |
| ICR | NO |
| Digital WDR | Yes |
| 2D/3D DNR | Yes |
| AGC | Yes |
| Global Exposure | Yes |
| Central Exposure | Yes |
| Auto White Balance | Yes |
| BLC | Yes |
| Front Light Compensation | Yes |
| Contrast | Yes |
| Saturation/Color Gain | Yes |
| Sharpness | Yes |
| Image Setting | Yes |
| Defect Correction | Auto |
| Language | Chinese and English |
| Angle Adjustment | Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360° |
| Others | |
| Power Supply | DC12V (± 15%) |
| Power Consumption | LED OFF : < 1W; LED ON : < 3W |
| Working Environment | - 30 °C ~ 50 °C, 10 % ~ 90 % (relative humidity) |
| Dimensions (mm) | 165.7 × 69 × 69 |
| Weight (net) | Approx. 0.37KG |

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

| | |
|-----------------|--------------------|
| Available Model | TD-7421TM3(SW/WR2) |
|-----------------|--------------------|